


AMF TOPIQ® Efficient Pro



- AMF TOPIQ® Efficient Pro is a very light stone wool panel with a modern, smooth surface.
- Excellent sound absorption (1.00 α_w)
- Excellent light reflectance (88%)
- ISO 4
- Ideal for offices, classrooms, learning applications and underground garages



AMF TOPIQ® EFFICIENT PRO



| Edge details | Board | Tegular 24/9 | 90 | | Tegulo | ar 15/90 | | |
|--|---|--------------------------------------|---------------|------------------|-------------|-------------------------|------|------|
| Additional edge details on request | <u> </u> | <u>∞</u> 24 | | | (m) | 5 | | |
| Thickness (mm) | 20 | 20 | | | 20 | | | |
| Dimensions (mm) Additional sizes on request | 600 x 600 625 x 625 1200 x 600 | 600 x 600 625 x 625 1200 x 600 | | | 625 | x 600 x 625 x 600 | | |
| System | Exposed demountable - System C | | | | | | | |
| Weight | 3.1 kg/m^2 | | | | | | | |
| Colour | White | | | | | | | |
| Sound absorption | EN ISO 354 α_{w} = 1.00 as per EN ISO 11654 - Frequency f (Hz) α_{p} NRC = 0.95 as per ASTM C 423 | | 125 0.45 | 250 0.90 | 500 1.00 | 1000 0.95 | 2000 | 4000 |
| Sound attenuation | EN ISO 10848-2 D _{n,f,w} = 25 dB as per EN ISO 717-1 CAC = 25 dB as per ASTM E 413-10 | | | | | | | |
| Sound reduction | EN ISO 10140-2 R _w = 15 dB as per EN ISO 717-1 | | | | | | | |
| Fire reaction | Euroclass A1 as per EN 13501-1 | | | | | | | |
| Light reflectance | 88% | | | | | | | |
| Humidity resistance | 100% RH | | | | | | | |
| Clean room | ISO 4 as per EN ISO 14644-1 | | | | | | | |
| Indoor air quality | EN 13964 | or Prediction | | | | | | |
| Cleanability | | | | | | | | |
| Sustainability | EC 1272/2008 Annes Q | w awalin | plauer-engel. | de /uz132 | | | | |

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.